


1237962



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

October 16, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/504,977

FILING DATE: *September 23, 2003*

RELATED PCT APPLICATION NUMBER: *PCT/US04/31491*

Certified by

Jon W Dudas

Acting Under Secretary of Commerce
for Intellectual Property
and Acting Director of the U.S.
Patent and Trademark Office



BEST AVAILABLE COPY

Please type a plus sign (+) inside this box → ☐

PTO/SB/16 (8-00)

Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

| INVENTOR(S) | | | | | |
|---|------------------------|---|--|--|----------------|
| Given Name (first and middle (if any)) | Family Name or Surname | Residence (City and either State or Foreign Country) | | | |
| John A. | Gelardi | Kennebunk, Maine | | | |
| <input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto | | | | | |
| TITLE OF THE INVENTION (280 characters max) | | | | | |
| Unit Dose Locking Container | | | | | |
| Direct all correspondence to: CORRESPONDENCE ADDRESS | | | | | |
| <input type="checkbox"/> Customer Number | | <input type="text"/> | | → <div>Place Customer Number Bar Code Label here</div> | |
| OR Type Customer Number here | | | | | |
| <input checked="" type="checkbox"/> Firm or Individual Name | James C. Wray | | | | |
| Address | 1493 Chain Bridge Road | | | | |
| Address | Suite 300 | | | | |
| City | McLean | State | VA | ZIP | 22101 |
| Country | US | Telephone | (703) 442-4800 | Fax | (703) 448-7397 |
| ENCLOSED APPLICATION PARTS (check all that apply) | | | | | |
| <input checked="" type="checkbox"/> Specification | Number of Pages | <input type="text" value="12"/> | <input type="checkbox"/> CD(s), Number | <input type="text"/> | |
| <input checked="" type="checkbox"/> Drawing(s) | Number of Sheets | <input type="text" value="13"/> | <input type="checkbox"/> Other (specify) | <input type="text"/> | |
| <input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76 | | | | | |
| METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one) | | | | | |
| <input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. | | | | FILING FEE AMOUNT (\$) | |
| <input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fees | | | | <input type="text" value="\$160.00"/> | |
| <input type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: <input type="text"/> | | | | | |
| <input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached. | | | | | |
| The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government. | | | | | |
| <input checked="" type="checkbox"/> No. | | | | | |
| <input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____ | | | | | |

19587 U.S. PTO
60/504977
09/23/03

BEST AVAILABLE COPY

Respectfully submitted,

SIGNATURE



TYPED / PRINTED NAME

James C. Wray

TELEPHONE

(703) 442-4800

Date

09/23/03

REGISTRATION NO.
(if appropriate)

22,693

Docket Number:

WESTVACO

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.



09/23/03

PTO/SB/17 (01-03)

Approved for use through 04/30/2003. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL for FY 2003

Effective 01/01/2003. Patent fees are subject to annual revision.

☐ Applicant claims small entity status. See 37 CFR 1.27

TOTAL AMOUNT OF PAYMENT (\$ 160.00

Complete if Known

Application Number
Filing Date 09/23/2003
First Named Inventor John A. Gelardi
Examiner Name
Art Unit
Attorney Docket No. WESTVACO

METHOD OF PAYMENT (check all that apply)

☒ Check ☐ Credit card ☐ Money Order ☐ Other ☐ None☐ Deposit Account:

Deposit
Account
Number
Deposit
Account
Name

The Commissioner is authorized to: (check all that apply)

☐ Charge fee(s) indicated below ☐ Credit any overpayments
☐ Charge any additional fee(s) during the pendency of this application
☐ Charge fee(s) indicated below, except for the filing fee to the above-identified deposit account.

FEE CALCULATION

1. BASIC FILING FEE

| Large Entity Fee Code (\$) | Small Entity Fee Code (\$) | Fee Description | Fee Paid |
|-------------------------------|-------------------------------|------------------------|----------|
| 1001 750 | 2001 375 | Utility filing fee | |
| 1002 330 | 2002 165 | Design filing fee | |
| 1003 520 | 2003 260 | Plant filing fee | |
| 1004 750 | 2004 375 | Reissue filing fee | |
| 1005 160 | 2005 80 | Provisional filing fee | 160 |

SUBTOTAL (1) (\$ 160.00

2. EXTRA CLAIM FEES FOR UTILITY AND REISSUE

Total Claims -20** = X =
Independent Claims -3** = X =
Multiple Dependent =

| Large Entity Fee Code (\$) | Small Entity Fee Code (\$) | Fee Description |
|-------------------------------|-------------------------------|--|
| 1202 18 | 2202 9 | Claims in excess of 20 |
| 1201 84 | 2201 42 | Independent claims in excess of 3 |
| 1203 280 | 2203 140 | Multiple dependent claim, if not paid |
| 1204 84 | 2204 42 | ** Reissue independent claims over original patent |
| 1205 18 | 2205 9 | ** Reissue claims in excess of 20 and over original patent |

SUBTOTAL (2) (\$)

**or number previously paid, if greater; For Reissues, see above

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity Small Entity

| Fee Code (\$) | Fee Code (\$) | Fee Description | Fee Paid |
|---------------|---------------|--|----------|
| 1051 130 | 2051 65 | Surcharge - late filing fee or oath | |
| 1052 50 | 2052 25 | Surcharge - late provisional filing fee or cover sheet | |
| 1053 130 | 2053 130 | Non-English specification | |
| 1812 2,520 | 2812 2,520 | For filing a request for <i>ex parte</i> reexamination | |
| 1804 920* | 2804 920* | Requesting publication of SIR prior to Examiner action | |
| 1805 1,840* | 2805 1,840* | Requesting publication of SIR after Examiner action | |
| 1251 110 | 2251 55 | Extension for reply within first month | |
| 1252 410 | 2252 205 | Extension for reply within second month | |
| 1253 930 | 2253 465 | Extension for reply within third month | |
| 1254 1,450 | 2254 725 | Extension for reply within fourth month | |
| 1255 1,970 | 2255 985 | Extension for reply within fifth month | |
| 1401 320 | 2401 160 | Notice of Appeal | |
| 1402 320 | 2402 160 | Filing a brief in support of an appeal | |
| 1403 280 | 2403 140 | Request for oral hearing | |
| 1451 1,510 | 2451 1,510 | Petition to institute a public use proceeding | |
| 1452 110 | 2452 55 | Petition to revive - unavoidable | |
| 1453 1,300 | 2453 650 | Petition to revive - unintentional | |
| 1501 1,300 | 2501 650 | Utility issue fee (or reissue) | |
| 1502 470 | 2502 235 | Design issue fee | |
| 1503 630 | 2503 315 | Plant issue fee | |
| 1460 130 | 2460 130 | Petitions to the Commissioner | |
| 1807 50 | 2807 50 | Processing fee under 37 CFR 1.17(q) | |
| 1806 180 | 2806 180 | Submission of Information Disclosure Stmt | |
| 8021 40 | 28021 40 | Recording each patent assignment per property (times number of properties) | |
| 1809 750 | 2809 375 | Filing a submission after final rejection (37 CFR 1.129(a)) | |
| 1810 750 | 2810 375 | For each additional invention to be examined (37 CFR 1.129(b)) | |
| 1801 750 | 2801 375 | Request for Continued Examination (RCE) | |
| 1802 900 | 2802 900 | Request for expedited examination of a design application | |

Other fee (specify)

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$)

SUBMITTED BY

(Complete if applicable)

Name (Print/Type) James C. Wray Registration No. 22,693 Telephone (703) 442-4800
Signature *James C. Wray* Date 09/23/2003

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

This collection of information is required by 37 CFR 1.17 and 1.27. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, Washington, DC 20231.

If you need assistance in completing the form, call 1-800-PTO-9199 (1-800-786-9199) and select option 2.

BEST AVAILABLE COPY

Unit Dose Locking Container

BACKGROUND OF THE INVENTION

Locking containers, especially childproof locking containers, in which multiple movements must be applied to open the container, have many uses. One use for locking containers is medicine containers. Locking caps on medicine bottles are well known. The caps usually require alignment and tipping of caps or axial pressure or inward radial squeezing while turning the caps to remove the caps from the containers and to provide access to medicine therein.

Many medicines are packaged in flat boxes, which are difficult to secure with childproof locks. Many medicines are sold in blister packs with bubbles formed in a plastic sheet sealed by a paper layer or foil which is punctured sequentially to release one dose from one bubble. When a cardboard sleeve is opened, the entire contents of the package is exposed, making all of the doses immediately available by puncturing the sealing sheet.

Needs exist for flat boxes that have locks which require multiple coordinated motions for opening. Needs exist for packages that present a limited number of doses at one time. Needs exist for inexpensive locking boxes.

SUMMARY OF THE INVENTION

Blister laminates are generally inserted and assembled in the manufacturing facilities through automation.

The invention allows local pharmacists to insert the blister medications into the casings. Casings can be re-used for prescription refills.

The invention is a child-resistant safety container for medications stored in a blister pack. A two-piece molded plastic container closed on 3 edges has a rectangular blister pack slidable through the open forth edge. Posts molded on one side are welded with the corresponding hollow cylinders molded on the other side. Energy directors may weld side edges. Two flexible springs are molded on one side and hold the blister pack against the other side of the container. At least one catch is molded on the same side and it fits through the opening that is a part of the blister pack. It prevents the blister pack from being fully removed. Pressing on the lever distorts the opening in the blister pack which can be slid out of the container. Ramps on the blacks of the catches depress the blister pack as it is slid inward.

This invention allows blister packs to be loaded into the case at the retail stores. It reduces costs of assembly. The casing can be re-used.

The new invention fulfills needs in single dose packaging.

A child-resistant safety container for medications stored in a blister pack has a two-piece molded plastic sleeve closed on three edges. A rectangular blister pack is slidable through the open fourth edge to expose a row of bubbles upon a manipulation of the parts. Posts molded on one side are inserted into and

welded with hollow cylinders molded on the other side. Energy directors may sonically weld side edges, as well as the posts and cylinders. A spring near the open edge fits through an opening in the blister pack tray and acts as a travel limit when the tray is slid out. Two flexible springs and four fixed rails are molded on a first side and hold the flat back of the blister pack against a second side of the sleeve. A molded catch on the second side near a closed end fits through an opening in the blister pack and prevents a fully inserted blister pack from sliding outward. Pressing on a lever distorts the blister pack so that the molded catch no longer engages the opening in the blister pack, which can be slid outward in the container to expose the blisters. A ramp on the back of the catch depresses the blister pack as it is slid inward. The leaf spring near the open end in the blister pack tray engages the opening and prevents the tray from being fully removed from the envelope.

The package has a sliding bubble container tray and a locking sleeve made from a base and a top. The tray is made from conventional bubble dose packing material with bubbles formed in a single layer plastic top holding pills on a sealed paper or foil base. The paper or foil is pushed in, cut or punched beneath one bubble at a time to release one dose. A standard bubble tray or blister pack is used and provides all necessary structural rigidity for functioning of the parts. The top is placed on the base. The pins are inserted in the cylinders and the plastic sleeve is welded shut. The bubble tray is placed in

the opening and is pushed inward past the limit spring and on the sliding guides of the base, between guiding cylinders. Springs formed in the top urge the bubble tray toward sliding ribs on the base. The catch holds the tray in the sleeve.

Pressing inward on the U-shaped tab on the base warps a part of the tray against the force of springs away from the catch on the base. The warping of the tray moves the hole away from the detent so that the tray may be slid outward through the open end of the sleeve.

The bubble tray is a conventional blister package. The whole cross-section of the plastic blister layer and the paper base provide strength. A constant containment element surrounds the blister package and forms the new locking package. Reverse pressure easily slides the blister package back into the containment element without manipulation of parts.

These and further and other objects and features of the invention are apparent in the disclosure, which includes the above and ongoing written specification, with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is an exploded top perspective view of the locking blister package.

Figure 2 is an exploded bottom perspective view of the locking package.

Figure 3 is a bottom perspective view of the closed locking package.

Figure 4 is a transparent top perspective view of the locking package with the blister panel moved partially outward from a slightly modified rounded closed end container.

Figure 5 is a top perspective transparent view of the container with the blister panel ready for loading.

Figure 6 is a transparent perspective bottom view of the container.

Figure 7 is a perspective top view of the locking package with the blister panel slid partially outward.

Figure 8 is a perspective bottom view of the locking package.

Figure 9 is an exploded bottom perspective view of the open container and bubble tray.

Figure 10 is an exploded perspective top view of the container and bubble tray.

Figure 11 is a bottom perspective assembled view of the closed package.

Figure 12 is an alternate package with multiple detent openings in the blister panel and a T-shaped release panel.

Figure 13 is a top perspective view of the package of Figure 12 showing positions of elements of the base, top and bubble tray.

Figure 14 is an exploded perspective view showing positions of elements of the base, top and bubble tray.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figures 1-3 are top and bottom exploded views and a bottom view of the locking package. As shown in Figure 1, a locking cassette container 10 has a sliding unit dose bubble package tray 12 with a locking sleeve 14. The locking sleeve has a base 16 and a top 18. A push U-shaped flap 20 is formed in an opening 21 and is connected to and integrally formed with the container by a thin resilient living hinge section 22. Pushing on the free end 24 of the push release flap frees the tray 12. The inside of free end 24 has a curved rim 25. Gripping the exposed end 26 of the tray in the recess 28 in the open end of the base and pulling outward while flap 20 is depressed enables the outward sliding.

The bubble package tray 12 has single dose-containing bubbles 30 arranged in two columns 32. The tray is constructed of the same materials with strengths and thicknesses as are conventional in bubble package trays sold in traditional rectangular cardboard sleeves, which are sealed on folded ends.

The bubble tray 12 has a hole 34, which releases the tray and prevents removal of the tray from the sleeve 14. Hole 34 positioned beyond the bubbles 30 cooperates with the detent 29 on the base to prevent outward movement of the tray until it is intentionally and properly released by pressing inward on flap 20. A rib at the end of the tray closes the open end 40 of the sleeve 14 when the tray is pushed inward, preventing access to the bubbles 30. The rib fits within cutout 28 and aids in outward sliding of the tray. Openings 46 in the sleeve top 18

allow the inward forming of springs 48 which press the tray against ribs on the base 16 and force hole 34 into engagement with retaining detent 29.

Figure 3 is a top view of the closed locking package 10. In the closed position the rib 38 closes open end 40 of the sleeve 14. The rib 38 presses against the inside of the top 18.

Cylinders 50 along side walls 52 of the base 16 are ready to receive pins 51 extending downward from an inside of the top. A dagger spring 54 centered in the top 18 near the open end 40 above the recess 28 at the open end of the base extends through the central hole 34 in the tray 12, to prevent complete removal of the tray. Detent 29 projects through the hole 34 to lock the tray 12 in the sleeve 14. Dagger spring 54 may be depressed by an inserted blade or card to withdraw the dagger spring from opening 36 for releasing an empty bubble panel 12 in preparation for inserting of a full bubble panel.

A rib at the inner end of the sleeve fits between springs 48. Inner ribs 58 inside the top 18 stabilize the tray as it is extended.

The top 18 is pressed onto the bottom, with the pins 51 pressed into the cylinders 50. Energy directors on insides of the cylinders and along the side walls 52 of the base 16 fuse and weld the top to the base under pressure and ultrasonic energy.

Figure 4 is a partially extended transparent sleeve top view of a closed modified rounded end locking package 11. In the

configuration shown in Figure 4, after the top 18 is assembled on the base 16, the tray is placed in the base.

Figure 5 is a transparent bottom view of the sleeve 14 of package 11 ready for insertion of the panel 12. The inside of the top 18 has ribs aligned between springs 48 to hold the tray against guides 64 on the inside of the base 16. The ribs and springs 48 are of sufficient height so that the bubbles are spaced from the inside of the top.

The head 24 of the U-shaped flap 20 is aligned between the springs 48 to warp the tray in the direction of the springs at gaps 66 between inner ends 68 of the ribs 58, and thus to release the hole 34 in tray 12 from the detent 29.

Figure 6 is an assembled bottom view of the container. Guides 64 on the inside of the base facilitate sliding of the tray. Ridges at the inside of base side walls 52 may fit inside of complementary side walls on the top 18. Push tray release flap 20 has a rib 25 on the inside of the head 24 of the flap. Rib 25 cooperates with the detent 29. As the rib 25 is pushed inward, an adjacent part of the bubble tray is warped toward the top 18 against the force of springs 48, releasing the tray from engagement with detent 29. Detent 29 has a straight or hook-shaped inward face 76 to hold the tray and prevent outward movement unless push bar 20 and rib 25 warp the tray away from the detents. Sloping outer face 78 on the detent warps the tray away from the detent upon inward movement of the tray, allowing free inward movement upon pushing on the free end of the tray.

Figure 7 is a partially opened top view of the locking package 11. Initials of days of the week between the bubbles serve as reminders. After a pill is removed from a bubble 30, the tray may be slid inward. During inward sliding, the sloped surface 78 urges the hole 34 and the tray 12 away from the detent 29.

Figure 8 is a cross-sectional bottom view of the locking package with the tray 12 moved partially outward.

Figure 9 is an exploded transparent bottom view of the container 11 and bubble tray 12. The tray 12 is shown in an intermediate position with respect to the base 16 in Figure 8. When fully inserted, hole 34 engages the detent 29.

Figure 10 is a top exploded transparent view of the container sleeve 14 and bubble tray 12. In Figure 10 the tray 12 is shown in an intermediate position.

Figure 11 is a bottom assembled view of the closed package 11. The push flap 20 is molded in an inward position in base 16 of the locking sleeve 14.

Figures 12-14 show bottom closed, top open and exploded views of a modified form of a container 1 showing the relative positions of elements of the base, top and tray. In Figures 12 and 13, the top 18 and base 16 are shown in assembled position. The T-shaped push bar 20 is molded inward, and is pressed outward by a tray. Springs 48 are molded inward in the top 18, so that they extend slightly beyond the inward extension of the ribs.

Thus, the springs support the tray in holding the T-bar outward. A rib at the outer end of the tray closes the open end 40.

The sloping back surfaces of the detents and the inward surfaces of ribs are radiused along with other tray-contacting surfaces to facilitate sliding of the tray or moving of the surfaces. The outer surface of the push bar has frictional grooves to aid in pushing the bar inward.

Figure 14 is an exploded detail showing positions of elements of the base, top and bubble tray. In Figure 14 the push bar 20 and the springs 48 are shown in positions after inserting the tray.

Parallel holes 34 engage parallel detents formed midway in the base slightly toward the open end 40 from the hole.

The top and base are pressed inward and welded together. The bubble tray is inserted. Pressing inward on the T-shaped bar 20 on the base 16 warps a part of the tray 12 between ribs against the force of springs 48 away from the base. The warping of the tray moves the holes 34 away from the detents 29 so that the tray 12 may be slid through the open end 40 of the sleeve 14. Releasing the bar 20 stops the tray in the next outward position.

The bubble tray is a conventional blister package with a hole or holes 34 added. The whole laminated cross-section of the plastic blister layer and the paper base provides strength. A constant containment element surrounds the blister package and forms the new locking package. Detents in one hole or holes in parallel series of holes prevent unwanted outward movement of the

tray. A push, pull and release sequence limits the exposure of blisters. Reverse pressure easily slides the blister tray back into the containment elements without manipulation of parts.

While the invention has been described with reference to specific embodiments, modifications and variations of the invention may be constructed without departing from the scope of the invention.

ABSTRACT OF THE DISCLOSURE

A package has a sliding bubble container tray and a locking sleeve made from a base and a top. The tray is made from conventional blister dose packaging material, with bubbles formed in a single layer plastic top holding pills on a sealing paper, board or foil layer. The sealing layer is punched beneath one bubble at a time to release one dose. The top and base are closed. Bubble trays are slid between the sliding guides of the base and between guiding cylinders and pushed inward until detents engage openings. Springs formed in the top urge the bubble tray toward the guides on the base. Pressing inward on a flap on the base moves a part of the tray against the force of springs away from the base. Warping the tray moves a hole away from a detent so that the tray may be slid through the open end of the sleeve. A constant containment element surrounds the blister package and forms the new locking package. Reverse pressure easily slides the blister package back into the containment element without manipulation of parts.




FIG. 1






FIG. 2






FIG. 3






FIG. 4




FIG. 5






FIG. 6







FIG. 7








FIG. 9




FIG. 10




FIG. 11

BEST AVAILABLE COPY





FIG. 12

FIG. 13

FIG. 14



BEST AVAILABLE COPY

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/031491

International filing date: 23 September 2004 (23.09.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/504,977
Filing date: 23 September 2003 (23.09.2003)

Date of receipt at the International Bureau: 25 October 2004 (25.10.2004)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse